

# Vibrocostipatori Tamping Rammer



Mc75 e MC72 sono dotati di contaore e contagiri

MC75 and MC72 are equipped with hour meters and tachometer

Powered by



Robin Industrial Products



Motorizzazione, consumabili  
e ricambi originali  
Motorization, accessories  
and original spare parts



MC75-H



MC72-S



Il sistema di filtrazione dell'aria a più stadi garantisce la massima affidabilità di funzionamento e sicurezza

Multi-stage air filtration system guarantees maximum operating reliability and safety



Opzionale carrello con ruote  
Trolley wheel as optional

L'impugnatura con ammortizzatore riduce la vibrazione.  
Protezione del motore con serbatoio del combustibile e  
leva dell'acceleratore integrata

Handle with heavy-duty shock absorber,  
reduces vibrations that are transmitted to the hand.  
Engine cover protection with integrated fuel tank and throttle

Vibrocostipatori / Tamping Rammer	MC 80	MC 72		MC 75	
Motore a 4 tempi / 4 stroke engine	Loncin 168	Subaru ER12	Honda GX100	Subaru EH 12-2D	Honda GX100
Tipo combustibile / Fuel type	Benzina / Gasolina				
Potenza massima motore / Max. engine power	5.5 hp	4.0 hp	3.0 hp	4.0 hp	3.0 hp
Giri motore / Engine revolutions	3000 rpm	3000-4100 rpm	3600 rpm	3000-4000 rpm	3600 rpm
Capacità serbatoio combustibile / Fuel tank capacity	2.8 l				
Consumo carburante / Fuel consumption	0.6 l/h	0.7 l/h	0.6 l/h	0.7 l/h	0.6 l/min.
Dimensione del piede / Plate size	345 x 285 mm				
Corsa del piede / Max. jumping stroke	65 mm	80 mm		85 mm	
Forza di compattazione / Impact force	10.7 kN	14.0 kN	12.0 kN	13.7 kN	13.0 kN
Frequenza battiti / Impact number	450-650 /min.	640-680 /min.		640-680 /min.	
Livello di rumore / Noise power level	105 dB	102 dB		103 dB	
Peso / Weight	79 kg	70 kg	68 kg	75 kg	72 kg
Dimensione l/L/a Dimensions l/L/h	480/ 760/ 1120	440/ 720/ 1100		430/ 720/ 1050	